

View Online at <https://aerobasegroup.com/nsn/3950-00-224-8433>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 motor controller

Environmental Protection:

Waterproof

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Powered

Capstan Spool Mounting Position:

Horizontal

Capstan Spool Surface Design:

Plain

Capstan Spool Quantity:

2

Load Limit At Selected Speed And Drum Location:

10000.0 pounds single speed first drum and 10000.0 pounds single speed second drum and 5000.0 pounds second speed first drum and 5000.0 pounds second speed second drum

Travel Rate Per Minute:

62.0 feet and 62.0 feet and 125.0 feet and 128.0 feet

Braking Method:

Electric

Power Requirement Rating:

30.00 horsepower

Largest Diameter And Location:

24.000 inches first spool and 24.000 inches second spool

Overall Length And Location:

21.000 inches first spool and 21.000 inches second spool

Cooling Method:

Non ventilated

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800