## NSN 3950-00-229-0714

Power Operated Drum Winch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3950-00-229-0714 **Prime Mover Quantity: Current Type:** Dc **Furnished Items And Quantity:** 1 motor controller and 1 pawl and ratchet **Environmental Protection:** Waterproof **Prime Mover Type:** Electric motor **Inclosure Type:** Fully enclosed **Duty Cycle:** Intermittent **Operation Method:** Power **Drum Flange To Flange Distance And Location:** 26,000 inches first drum **Drum Diameter And Location:** 20.000 inches first drum **Drum Flange Diameter And Location:** 37.000 inches first drum **Capstan Spool Mounting Position:** Horizontal **Capstan Spool Surface Design:** Plain **Capstan Spool Quantity: Load Limit At Selected Speed And Drum Location:** 14000.0 pounds single speed first drum and 7500.0 pounds second speed first drum **Travel Rate Per Minute:** 105.0 feet and 185.0 feet **Power Requirement Rating:** 50.00 horsepower **Drum Surface Design:** Plain **Largest Diameter And Location:** 18.000 inches first spool

**Overall Length And Location:** 16.250 inches first spool

**Cooling Method:** 

Non ventilated

## NSN 3950-00-229-0714

Power Operated Drum Winch - Page 2 of 2



Voltage In Volts:
230.0
Special Features:
Has variable speed electric motor
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A02800