

View Online at <https://aerobasegroup.com/nsn/3950-00-229-0715>

Prime Mover Quantity:

1

Current Type:

Dc

Furnished Items And Quantity:

1 pawl and ratchet and 1 motor controller

Environmental Protection:

Waterproof

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Drum Flange To Flange Distance And Location:

26.000 inches first drum

Drum Diameter And Location:

20.000 inches first drum

Drum Flange Diameter And Location:

37.000 inches first drum

Capstan Spool Mounting Position:

Horizontal

Capstan Spool Surface Design:

Plain

Capstan Spool Quantity:

1

Load Limit At Selected Speed And Drum Location:

14000.0 pounds single speed first drum and 7500.0 pounds second speed first drum

Travel Rate Per Minute:

105.0 feet and 185.0 feet

Power Requirement Rating:

50.00 horsepower

Drum Surface Design:

Plain

Largest Diameter And Location:

18.000 inches first spool

Overall Length And Location:

16.000 inches first spool

Cooling Method:

Non ventilated

Voltage In Volts:

230.0

Special Features:

Has variable speed electric motor

Reference Number Differentiating Characteristics:

As differentiated by westinghouse motor and controller

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A02800