

View Online at <https://aerobasegroup.com/nsn/3950-00-229-0719>

**Prime Mover Quantity:**

1

**Current Type:**

Dc

**Furnished Items And Quantity:**

1 motor controller

**Environmental Protection:**

Waterproof

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Power

**Drum Flange To Flange Distance And Location:**

16.000 inches first drum and 16.000 inches second drum

**Drum Diameter And Location:**

18.000 inches first drum and 18.000 inches second drum

**Drum Flange Diameter And Location:**

26.000 inches first drum and 26.000 inches second drum

**Capstan Spool Mounting Position:**

Horizontal

**Capstan Spool Surface Design:**

Plain

**Capstan Spool Quantity:**

1

**Load Limit At Selected Speed And Drum Location:**

1850.0 pounds single speed first drum and 1850.0 pounds single speed second drum

**Travel Rate Per Minute:**

100.0 feet

**Power Requirement Rating:**

20.00 horsepower

**Drum Surface Design:**

Plain

**Largest Diameter And Location:**

17.750 inches first spool

**Overall Length And Location:**

15.000 inches first spool

**Cooling Method:**

Any acceptable

**Voltage In Volts:**

115.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800