

View Online at <https://aerobasegroup.com/nsn/3950-00-229-0723>

**Prime Mover Quantity:**

1

**Current Type:**

Dc

**Furnished Items And Quantity:**

1 motor controller and 1 pawl and ratchet

**Environmental Protection:**

Waterproof

**Unpackaged Unit Length:**

144.00 inches

**Unpackaged Unit Width:**

54.63 inches

**Unpackaged Unit Height:**

100.00 inches

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Power

**Drum Flange To Flange Distance And Location:**

23.750 inches first drum and 23.750 inches second drum

**Drum Diameter And Location:**

20.000 inches first drum and 20.000 inches second drum

**Drum Flange Diameter And Location:**

36.000 inches first drum and 36.000 inches second drum

**Capstan Spool Mounting Position:**

Horizontal

**Capstan Spool Style:**

Straight head

**Capstan Spool Surface Design:**

Plain

**Capstan Spool Quantity:**

2

**Load Limit At Selected Speed And Drum Location:**

12500.0 pounds single speed first drum and 12500.0 pounds second speed second drum

**Travel Rate Per Minute:**

110.0 feet and 185.0 feet

**Braking Method:**

Electric

**Clutch Type:**

Friction

**Power Requirement Rating:**

50.00 horsepower

**Drum Surface Design:**

Plain

**Largest Diameter And Location:**

18.000 inches first spool and 18.000 inches second spool

**Overall Length And Location:**

15.000 inches first spool and 15.000 inches second spool

**Transmission Type:**

Manual

**Cooling Method:**

Any acceptable

**Voltage In Volts:**

230.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800