NSN 3950-00-229-0723

Power Operated Drum Winch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3950-00-229-0723

Prime Mover Quantity:
1
Current Type:
Dc
Furnished Items And Quantity:
1 motor controller and 1 pawl and ratchet
Environmental Protection:
Waterproof
Unpackaged Unit Length:
144.00 inches
Unpackaged Unit Width:
54.63 inches
Unpackaged Unit Height:
100.00 inches
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Duty Cycle:
Intermittent
Operation Method:
Power
Drum Flange To Flange Distance And Location:
23.750 inches first drum and 23.750 inches second drum
Drum Diameter And Location:
20.000 inches first drum and 20.000 inches second drum
Drum Flange Diameter And Location:
36.000 inches first drum and 36.000 inches second drum
Capstan Spool Mounting Position:
Horizontal
Capstan Spool Style:
Straight head
Capstan Spool Surface Design:
Plain
Capstan Spool Quantity:
2
Load Limit At Selected Speed And Drum Location:
12500.0 pounds single speed first drum and 12500.0 pounds second speed second drum
Travel Rate Per Minute:
110.0 feet and 185.0 feet
Braking Method:
Electric

NSN 3950-00-229-0723Power Operated Drum Winch - Page 2 of 2



Clutch Type:
Friction
Power Requirement Rating:
50.00 horsepower
Drum Surface Design:
Plain
Largest Diameter And Location:
18.000 inches first spool and 18.000 inches second spool
Overall Length And Location:
15.000 inches first spool and 15.000 inches second spool
Transmission Type:
Manual
Cooling Method:
Any acceptable
Voltage In Volts:
230.0
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
402800