

View Online at <https://aerobasegroup.com/nsn/3950-00-231-0508>

Prime Mover Quantity:

1

Current Type:

Dc

Furnished Items And Quantity:

1 motor controller and 1 level winding device and 1 constant tensioning device and 1 remote control

Environmental Protection:

Waterproof

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Drum Flange To Flange Distance And Location:

27.500 inches first drum

Drum Diameter And Location:

38.000 inches first drum

Drum Flange Diameter And Location:

60.000 inches first drum

Capstan Spool Mounting Position:

Horizontal

Capstan Spool Style:

Single head

Capstan Spool Surface Design:

Plain

Capstan Spool Quantity:

2

Load Limit At Selected Speed And Drum Location:

100000.0 pounds single speed first drum and 3000.0 pounds second speed first drum

Travel Rate Per Minute:

10.0 feet and 400.0 feet

Braking Method:

Electric

Clutch Type:

Friction

Power Requirement Rating:

50.00 horsepower

Drum Surface Design:

Grooved

Largest Diameter And Location:

17.000 inches first spool and 17.000 inches second spool

Overall Length And Location:

18.000 inches first spool and 18.000 inches second spool

Cooling Method:

Any acceptable

Voltage In Volts:

230.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800