

View Online at <https://aerobasegroup.com/nsn/3950-00-231-0508>

**Prime Mover Quantity:**

1

**Current Type:**

Dc

**Furnished Items And Quantity:**

1 motor controller and 1 level winding device and 1 constant tensioning device and 1 remote control

**Environmental Protection:**

Waterproof

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Power

**Drum Flange To Flange Distance And Location:**

27.500 inches first drum

**Drum Diameter And Location:**

38.000 inches first drum

**Drum Flange Diameter And Location:**

60.000 inches first drum

**Capstan Spool Mounting Position:**

Horizontal

**Capstan Spool Style:**

Single head

**Capstan Spool Surface Design:**

Plain

**Capstan Spool Quantity:**

2

**Load Limit At Selected Speed And Drum Location:**

100000.0 pounds single speed first drum and 3000.0 pounds second speed first drum

**Travel Rate Per Minute:**

10.0 feet and 400.0 feet

**Braking Method:**

Electric

**Clutch Type:**

Friction

**Power Requirement Rating:**

50.00 horsepower

**Drum Surface Design:**

Grooved

**Largest Diameter And Location:**

17.000 inches first spool and 17.000 inches second spool

**Overall Length And Location:**

18.000 inches first spool and 18.000 inches second spool

**Cooling Method:**

Any acceptable

**Voltage In Volts:**

230.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02800