

View Online at <https://aerobasegroup.com/nsn/3950-00-241-8092>

Tire Type:

Solid rubber

Power Unit Type:

Gasoline engine

Boom Design:

Telescoping

Extended Length:

18.000 feet

Retracted Length:

12.000 feet

Maximum Load Rating:

10.000 pounds

Boom Type:

Revolving

Boom Capacity At Specificationified Radius:

15000 lb boom capacity at 5 ft radius, 14000 lb boom capacity at 5-1/2 ft radius, 13000 lb boom capacity at 6 ft radius, 12000 lb boom capacity at 6-1/2 ft radius, 11000 lb boom capacity at 7 ft radius, 10000 lb boom capacity at 7-1/2 ft radius, 9000 lb boom capacity at 8 ft radius, 8000 lb boom capacity at 8-1/2 ft radius, 7000 lb boom capacity at 9-1/2 ft radius, 6000 lb boom capacity at 10 ft radius, 5000 lb boom capacity at 11-1/2 ft radius, 4000 lb boom capacity at 13 ft radius, 3000 lb boom capacity at 15 ft radius, 2000 lb boom capacity at 18 ft radius

Reference Number Differentiating Characteristics:

Except mounted on international i-9 tractor

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T340-d