

View Online at <https://aerobasegroup.com/nsn/3950-00-241-8092>

**Tire Type:**

Solid rubber

**Power Unit Type:**

Gasoline engine

**Boom Design:**

Telescoping

**Extended Length:**

18.000 feet

**Retracted Length:**

12.000 feet

**Maximum Load Rating:**

10.000 pounds

**Boom Type:**

Revolving

**Boom Capacity At Specificationified Radius:**

15000 lb boom capacity at 5 ft radius, 14000 lb boom capacity at 5-1/2 ft radius, 13000 lb boom capacity at 6 ft radius, 12000 lb boom capacity at 6-1/2 ft radius, 11000 lb boom capacity at 7 ft radius, 10000 lb boom capacity at 7-1/2 ft radius, 9000 lb boom capacity at 8 ft radius, 8000 lb boom capacity at 8-1/2 ft radius, 7000 lb boom capacity at 9-1/2 ft radius, 6000 lb boom capacity at 10 ft radius, 5000 lb boom capacity at 11-1/2 ft radius, 4000 lb boom capacity at 13 ft radius, 3000 lb boom capacity at 15 ft radius, 2000 lb boom capacity at 18 ft radius

**Reference Number Differentiating Characteristics:**

Except mounted on international i-9 tractor

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T340-d