

View Online at <https://aerobasegroup.com/nsn/3950-00-254-5698>

Prime Mover Quantity:

1

Current Type:

Ac

Environmental Protection:

Any acceptable

Maximum Lift Height:

20.0 feet

Flange Width:

Between 3.330 inches and 5.000 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Load Limit At Selected Speed And Drum Location:

2000.0 pounds single speed first drum

Travel Rate Per Minute:

19.0 feet

Mechanical Advantage Method:

Multiple gear

Braking Method:

Electric

Hook Quantity:

2

Load Element Quantity Per Hook:

1

Center To Center Distance Between Load Elements:

Any acceptable

Power Requirement Rating:

1.50 horsepower

Suspension Mounting Method:

Trolley

Trolley Suspension Style:

Plain, standard i beam, wheels vertical

Trolley Type:

Plain

Track Height:

Between 6.000 inches and 12.000 inches

Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:

Any acceptable

Wheel Center To Center Distance:

Any acceptable

Mounting Position:

Parallel

Cooling Method:

Self-ventilated

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

Trolley has 48.000 in. radius; w/wheel type current collectors and push button pendant control; electric motor, 30 minutes 55.0 @degree temperature rise, nongovernment document data: hmi 100-11878

Frequency In Hertz:

60.0

Nongovernment Document Data:

Hmi 100-11878

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800