

View Online at <https://aerobasegroup.com/nsn/3950-00-257-5223>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 motor controller

Environmental Protection:

Splashtight

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Powered

Capstan Spool Mounting Position:

Horizontal

Capstan Spool Surface Design:

Plain

Capstan Spool Quantity:

2

Load Limit At Selected Speed And Drum Location:

3000.0 pounds single speed first drum and 3000.0 pounds second speed first drum and 3000.0 pounds single speed second drum

Travel Rate Per Minute:

60.0 feet and 120.0 feet

Braking Method:

Electric

Power Requirement Rating:

30.00 horsepower

Overall Length And Location:

12.000 inches first spool and 12.000 inches second spool

Smallest Diameter And Location:

15.125 inches first spool and 15.125 inches second spool

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Test Data Document:

81349-mil-w-15802 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800