

View Online at <https://aerobasegroup.com/nsn/3950-00-257-5223>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Furnished Items And Quantity:**

1 motor controller

**Environmental Protection:**

Splashtight

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Powered

**Capstan Spool Mounting Position:**

Horizontal

**Capstan Spool Surface Design:**

Plain

**Capstan Spool Quantity:**

2

**Load Limit At Selected Speed And Drum Location:**

3000.0 pounds single speed first drum and 3000.0 pounds second speed first drum and 3000.0 pounds single speed second drum

**Travel Rate Per Minute:**

60.0 feet and 120.0 feet

**Braking Method:**

Electric

**Power Requirement Rating:**

30.00 horsepower

**Overall Length And Location:**

12.000 inches first spool and 12.000 inches second spool

**Smallest Diameter And Location:**

15.125 inches first spool and 15.125 inches second spool

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Test Data Document:**

81349-mil-w-15802 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800