

View Online at <https://aerobasegroup.com/nsn/3950-00-257-5224>

**Prime Mover Quantity:**

1

**Current Type:**

Dc

**Furnished Items And Quantity:**

1 motor controller

**Environmental Protection:**

Splashtight

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Power

**Capstan Spool Mounting Position:**

Horizontal

**Capstan Spool Style:**

Single head

**Capstan Spool Surface Design:**

Plain

**Capstan Spool Quantity:**

2

**Load Limit At Selected Speed And Drum Location:**

1250.0 pounds single speed first drum and 1250.0 pounds single speed second drum

**Travel Rate Per Minute:**

125.0 feet

**Mechanical Advantage Method:**

Worm gear

**Braking Method:**

Electric

**Power Requirement Rating:**

15.00 horsepower

**Largest Diameter And Location:**

12.000 inches first spool and 12.000 inches second spool

**Overall Length And Location:**

10.625 inches first spool and 10.625 inches second spool

**Cooling Method:**

Self-ventilated

**Voltage In Volts:**

230.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800