NSN 3950-00-276-7407

Windlass - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3950-00-276-7407

Prime Mover Quantity:
1
Current Type:
Dc
Furnished Items And Quantity:
1 motor controller
Environmental Protection:
Dripproof
Chain Type:
Die lock link
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Duty Cycle:
Intermittent
Operation Method:
Power
Capstan Spool Mounting Position:
Vertical
Capstan Spool Quantity:
1
Whelped Wheel Quantity:
1
Whelp Quantity:
7
Load Limit At Selected Speed And Drum Location:
10600.0 pounds single speed first drum
Travel Rate Per Minute:
30.0 feet
Braking Method:
Manual and electric
Shaft Mounting Position:
Vertical
Power Requirement Rating:
20.00 horsepower
Largest Diameter And Location:
24.250 inches first spool
Overall Length And Location:
30.375 inches first spool
Chain Material Diameter:
1.250 inches

NSN 3950-00-276-7407

Windlass - Page 2 of 2

A02800



Cooling Method:
Nonventilated
Voltage In Volts:
230.0
Reference Number Differentiating Characteristics:
As differentiated by electric motor data
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: