

View Online at <https://aerobasegroup.com/nsn/3950-00-292-9937>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Environmental Protection:**

Any acceptable

**Chain Type:**

Roller link

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Powered

**Load Limit At Selected Speed And Drum Location:**

2000.0 pounds single speed first drum

**Travel Rate Per Minute:**

8.0 feet

**Mechanical Advantage Method:**

Spur gear

**Braking Method:**

Electric

**Hook Quantity:**

1

**Load Element Quantity Per Hook:**

1

**Power Requirement Rating:**

0.50 horsepower

**Suspension Mounting Method:**

Hook

**Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:**

24.000 inches

**Mounting Position:**

Any acceptable

**Cooling Method:**

Non-ventilated

**Product Name:**

Feat

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

10.0 feet height of lift, motor controller included

**Frequency In Hertz:**

60.0

**Specification Or Standard:**

2 type and 2 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02800