

View Online at <https://aerobasegroup.com/nsn/3950-00-292-9938>

Prime Mover Quantity:

1

Current Type:

Ac

Environmental Protection:

Any acceptable

Chain Type:

Roller link

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Load Limit At Selected Speed And Drum Location:

2000.0 pounds single speed first drum

Travel Rate Per Minute:

17.0 feet

Mechanical Advantage Method:

Multiple gear

Braking Method:

Automatic

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Power Requirement Rating:

1.00 horsepower

Suspension Mounting Method:

Hook

Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:

Any acceptable

Chain Material Diameter:

Any acceptable

Mounting Position:

Swivel

Cooling Method:

Any acceptable

Voltage In Volts:

220.0

Phase:

Three

Special Features:

30.0 ft h of lift, hooks w/safety latches, pendant rope controls, 30 min 55 degrees c motor temp rise, upper limit switch, max weight 100 lbs,
nongovernment document data: hmi400-18878

Frequency In Hertz:

60.0

Nongovernment Document Data:

Hmi400-18878

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800