

View Online at <https://aerobasegroup.com/nsn/3950-00-376-1588>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 motor controller and 2 level winding device

Environmental Protection:

Dripproof

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Drum Flange To Flange Distance And Location:

37.000 inches first drum and 37.000 inches second drum and 8.500 inches third drum

Drum Diameter And Location:

24.000 inches first drum and 24.000 inches second drum and 24.000 inches third drum

Drum Flange Diameter And Location:

48.000 inches first drum and 48.000 inches second drum and 48.000 inches third drum

Capstan Spool Mounting Position:

Horizontal

Capstan Spool Style:

Single head

Capstan Spool Surface Design:

Plain

Capstan Spool Quantity:

2

Load Limit At Selected Speed And Drum Location:

8000.0 pounds single speed third drum err-100 err-100

Travel Rate Per Minute:

135.0 feet

Braking Method:

Manual

Clutch Type:

Friction

Power Requirement Rating:

40.00 horsepower

Drum Surface Design:

Plain

Largest Diameter And Location:

15.000 inches first spool

Overall Length And Location:

12.000 inches first spool

Transmission Type:

Automatic

Cooling Method:

Self-ventilated

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800