

View Online at <https://aerobasegroup.com/nsn/3950-00-391-9487>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Furnished Items And Quantity:**

1 motor controller

**Environmental Protection:**

Splashtight

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Power

**Drum Flange To Flange Distance And Location:**

14.000 inches first drum and 14.000 inches second drum

**Drum Diameter And Location:**

24.000 inches first drum and 24.000 inches second drum

**Capstan Spool Mounting Position:**

Horizontal

**Capstan Spool Surface Design:**

Plain

**Capstan Spool Quantity:**

2

**Load Limit At Selected Speed And Drum Location:**

22700.0 pounds single speed first drum

**Travel Rate Per Minute:**

15.0 feet

**Power Requirement Rating:**

20.00 horsepower

**Drum Surface Design:**

Grooved

**Largest Diameter And Location:**

24.000 inches first spool and 24.000 inches second spool

**Overall Length And Location:**

20.875 inches first spool and 20.875 inches second spool

**Cooling Method:**

Non ventilated

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800