

View Online at <https://aerobasegroup.com/nsn/3950-00-391-9487>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 motor controller

Environmental Protection:

Splashtight

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Drum Flange To Flange Distance And Location:

14.000 inches first drum and 14.000 inches second drum

Drum Diameter And Location:

24.000 inches first drum and 24.000 inches second drum

Capstan Spool Mounting Position:

Horizontal

Capstan Spool Surface Design:

Plain

Capstan Spool Quantity:

2

Load Limit At Selected Speed And Drum Location:

22700.0 pounds single speed first drum

Travel Rate Per Minute:

15.0 feet

Power Requirement Rating:

20.00 horsepower

Drum Surface Design:

Grooved

Largest Diameter And Location:

24.000 inches first spool and 24.000 inches second spool

Overall Length And Location:

20.875 inches first spool and 20.875 inches second spool

Cooling Method:

Non ventilated

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800