

View Online at <https://aerobasegroup.com/nsn/3950-00-401-4068>

Prime Mover Quantity:

1

Current Type:

Ac

Environmental Protection:

Any acceptable

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Drum Flange To Flange Distance And Location:

5.938 inches first drum

Drum Diameter And Location:

2.875 inches first drum

Drum Flange Diameter And Location:

6.000 inches first drum

Load Limit At Selected Speed And Drum Location:

500.0 pounds single speed first drum

Travel Rate Per Minute:

50.0 feet

Braking Method:

Electric

Power Requirement Rating:

0.75 horsepower

Drum Surface Design:

Plain

Cooling Method:

Any acceptable

Voltage In Volts:

115.0 and 230.0

Phase:

Single

Special Features:

14.625 in. Lg o/a parallel to drum; 14.750 in. W o/a right angle to drum; 11.125 in. O/a h; w/toggle lever control; motor duty rating 30 minutes 55.0 degrees c; @drum capaci type 200.0 ft of 0.250 in. Wire rope; drum capaci type 110.0 ft of 0.312 in. Wire rope

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800