

View Online at <https://aerobasegroup.com/nsn/3950-00-403-1302>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Furnished Items And Quantity:**

1 motor controller and 1 remote control

**Environmental Protection:**

Watertight

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Continuous

**Operation Method:**

Power

**Drum Flange To Flange Distance And Location:**

15.000 inches first drum

**Drum Diameter And Location:**

24.000 inches stylet knob blank

**Drum Flange Diameter And Location:**

38.000 inches first drum

**Capstan Spool Mounting Position:**

Horizontal

**Capstan Spool Style:**

Single head

**Capstan Spool Surface Design:**

Plain

**Capstan Spool Quantity:**

2

**Load Limit At Selected Speed And Drum Location:**

8500.0 pounds single speed first drum

**Travel Rate Per Minute:**

300.0 feet

**Braking Method:**

Manual

**Power Requirement Rating:**

75.00 horsepower

**Drum Surface Design:**

Plain

**Largest Diameter And Location:**

15.000 inches middle cannula not applicable and 15.000 inches middle cannula any acceptable

Overall Length And Location:

12.000 inches middle cannula not applicable and 12.000 inches middle cannula any acceptable

Cooling Method:

Any acceptable

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800