

View Online at <https://aerobasegroup.com/nsn/3950-00-510-9080>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 motor controller

Environmental Protection:

Any acceptable

Maximum Lift Height:

18.000 feet

Flange Width:

Between 4.000 inches and 6.000 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Powered

Load Limit At Selected Speed And Drum Location:

6000.0 pounds single speed first drum

Travel Rate Per Minute:

28.0 feet

Mechanical Advantage Method:

Multi-gear

Braking Method:

Manual and automatic

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Center To Center Distance Between Load Elements:

Any acceptable

Power Requirement Rating:

5.00 horsepower

Suspension Mounting Method:

Trolley

Trolley Suspension Style:

Plain, standard i beam, wheels vertical

Trolley Type:

Plain

Track Height:

Between 8.000 inches and 18.000 inches

Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:

Any acceptable

Wheel Center To Center Distance:

Any acceptable

Mounting Position:

Parallel

Cooling Method:

Non ventilated

Voltage In Volts:

230.0

Phase:

Three

Special Features:

Stream (std tension replen)

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800