

View Online at <https://aerobasegroup.com/nsn/3950-00-580-8608>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 pawl and ratchet

Environmental Protection:

Dripproof

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Drum Flange To Flange Distance And Location:

20.000 inches first drum and 20.000 inches second drum

Drum Diameter And Location:

24.000 inches first drum and 24.000 inches second drum

Drum Flange Diameter And Location:

38.000 inches first drum and 38.000 inches second drum

Capstan Spool Mounting Position:

Horizontal

Capstan Spool Style:

Single head

Capstan Spool Surface Design:

Plain

Capstan Spool Quantity:

1

Load Limit At Selected Speed And Drum Location:

7400.0 pounds zero to full speed first drum and 7400.0 pounds zero to full speed second drum

Travel Rate Per Minute:

220.0 feet

Braking Method:

Manual

Clutch Type:

Positive

Power Requirement Rating:

50.00 horsepower

Drum Surface Design:

Plain

Largest Diameter And Location:

15.000 inches first spool

Overall Length And Location:

12.000 inches first spool

Transmission Type:

Automatic

Cooling Method:

Self-ventilated

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800