

View Online at <https://aerobasegroup.com/nsn/3950-00-600-1812>

Prime Mover Quantity:

1

Current Type:

Dc

Furnished Items And Quantity:

4 pawl and ratchet and 1 level winding device and 1 motor controller

Environmental Protection:

Watertight

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Drum Flange To Flange Distance And Location:

13.333 inches first drum and 13.333 inches second drum and 6.000 inches third drum and 7.000 inches fourth drum

Drum Diameter And Location:

10.000 inches first drum and 10.000 inches second drum and 15.000 inches third drum and 10.000 inches fourth drum

Drum Flange Diameter And Location:

37.000 inches first drum and 37.000 inches second drum and 29.000 inches third drum and 37.000 inches fourth drum

Capstan Spool Mounting Position:

Vertical

Capstan Spool Surface Design:

Plain

Capstan Spool Quantity:

2

Load Limit At Selected Speed And Drum Location:

7500.0 pounds zero to full speed first drum and 7500.0 pounds zero to full speed second drum and 7500.0 pounds zero to full speed third drum and 7500.0 pounds zero to full speed fourth drum

Travel Rate Per Minute:

100.0 feet

Power Requirement Rating:

30.00 horsepower

Drum Surface Design:

Plain

Largest Diameter And Location:

15.000 inches first spool and 15.000 inches second spool

Overall Length And Location:

12.500 inches first spool and 12.500 inches second spool

Cooling Method:

Non ventilated

Voltage In Volts:

115.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800