

View Online at <https://aerobasegroup.com/nsn/3950-00-618-2902>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 motor controller and 1 remote control and 1 boom swinger

Environmental Protection:

Watertight

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Continuous

Operation Method:

Power

Drum Flange To Flange Distance And Location:

20.000 inches first drum

Drum Diameter And Location:

24.000 inches stylet knob blank

Drum Flange Diameter And Location:

34.000 inches first drum

Load Limit At Selected Speed And Drum Location:

14800.0 pounds single speed first drum and 7400.0 pounds second speed first drum

Travel Rate Per Minute:

220.0 feet and 440.0 feet

Braking Method:

Manual

Power Requirement Rating:

100.00 horsepower

Drum Surface Design:

Plain

Transmission Type:

Manual

Cooling Method:

Any acceptable

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

As differentiated by inclusion of motor controller

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800