

View Online at <https://aerobasegroup.com/nsn/3950-00-641-2657>

Prime Mover Quantity:

1

Current Type:

Ac

Environmental Protection:

Dripproof

Maximum Lift Height:

20.0 feet

Flange Width:

6.000 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Duty Cycle:

Continuous

Operation Method:

Power

Load Limit At Selected Speed And Drum Location:

1000.0 pounds single speed first drum

Travel Rate Per Minute:

38.0 feet

Mechanical Advantage Method:

Differential

Braking Method:

Electric

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Center To Center Distance Between Load Elements:

Any acceptable

Power Requirement Rating:

2.00 horsepower

Suspension Mounting Method:

Trolley

Trolley Suspension Style:

Plain, wide flange i beam wheels vertical

Trolley Type:

Plain

Track Height:

8.000 inches

Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:

24.375 inches

Wheel Center To Center Distance:

Any acceptable

Mounting Position:

Parallel

Cooling Method:

Air to air cooled

Voltage In Volts:

220.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800