

View Online at <https://aerobasegroup.com/nsn/3950-00-787-2070>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Furnished Items And Quantity:**

1 motor controller

**Environmental Protection:**

Splashtight

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Power

**Drum Flange To Flange Distance And Location:**

15.000 inches first drum

**Drum Diameter And Location:**

24.000 inches stylet knob blank

**Drum Flange Diameter And Location:**

37.000 inches first drum

**Load Limit At Selected Speed And Drum Location:**

6000.0 pounds single speed first drum and 3000.0 pounds second speed first drum

**Travel Rate Per Minute:**

250.0 feet and 500.0 feet

**Braking Method:**

Manual

**Clutch Type:**

Friction

**Power Requirement Rating:**

75.00 horsepower

**Drum Surface Design:**

Grooved

**Transmission Type:**

Manual

**Cooling Method:**

Any acceptable

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Reference Number Differentiating Characteristics:**

Without gypsy head

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02800