

View Online at <https://aerobasegroup.com/nsn/3950-00-837-5805>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Environmental Protection:**

Watertight

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Power

**Drum Flange To Flange Distance And Location:**

15.000 inches first drum

**Drum Diameter And Location:**

24.000 inches first drum

**Drum Flange Diameter And Location:**

38.000 inches first drum

**Capstan Spool Mounting Position:**

Horizontal

**Capstan Spool Style:**

Single head

**Capstan Spool Surface Design:**

Plain

**Capstan Spool Quantity:**

1

**Load Limit At Selected Speed And Drum Location:**

8500.0 pounds single speed first drum

**Travel Rate Per Minute:**

300.0 feet

**Clutch Type:**

Friction

**Power Requirement Rating:**

75.00 horsepower

**Drum Surface Design:**

Plain

**Largest Diameter And Location:**

15.000 inches first spool

**Overall Length And Location:**

12.000 inches first spool

**Transmission Type:**

Automatic

**Cooling Method:**

Any acceptable

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800