

View Online at <https://aerobasegroup.com/nsn/3950-00-860-0923>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Furnished Items And Quantity:**

1 motor controller

**Environmental Protection:**

Splashtight

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Continuous

**Operation Method:**

Power

**Capstan Spool Mounting Position:**

Horizontal

**Capstan Spool Style:**

Single head

**Capstan Spool Surface Design:**

Plain

**Capstan Spool Quantity:**

2

**Load Limit At Selected Speed And Drum Location:**

550.0 pounds single speed first drum and 550.0 pounds single speed second drum

**Travel Rate Per Minute:**

40.0 feet

**Mechanical Advantage Method:**

Worm gear

**Braking Method:**

Electric

**Power Requirement Rating:**

2.00 horsepower

**Largest Diameter And Location:**

8.000 inches first spool and 8.000 inches second spool

**Overall Length And Location:**

8.500 inches first spool and 8.500 inches second spool

**Cooling Method:**

Any acceptable

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800