

View Online at <https://aerobasegroup.com/nsn/3950-00-898-4736>

Prime Mover Quantity:

1

Current Type:

Ac

Environmental Protection:

Any acceptable

Maximum Lift Height:

29.8 feet

Flange Width:

2.875 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Load Limit At Selected Speed And Drum Location:

1000.0 pounds single speed first drum

Travel Rate Per Minute:

32.0 feet

Mechanical Advantage Method:

Worm gear

Braking Method:

Electric

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Power Requirement Rating:

1.00 horsepower

Suspension Mounting Method:

Trolley

Trolley Suspension Style:

Plain, wide flange i beam wheels vertical

Trolley Type:

Plain

Track Height:

Between 5.000 inches and 10.000 inches

Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:

20.750 inches

Wheel Center To Center Distance:

7.250 inches

Maximum Load Rating:

1000.0 pounds

Mounting Position:

Parallel

Cooling Method:

Self-ventilated

Voltage In Volts:

230.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800