

View Online at <https://aerobasegroup.com/nsn/3950-00-907-6406>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Environmental Protection:**

Any acceptable

**Chain Type:**

Proof coil

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Power

**Load Limit At Selected Speed And Drum Location:**

2000.0 pounds single speed first drum

**Travel Rate Per Minute:**

16.0 feet

**Mechanical Advantage Method:**

Multiple gear

**Braking Method:**

Automatic

**Hook Quantity:**

1

**Load Element Quantity Per Hook:**

1

**Power Requirement Rating:**

1.000 horsepower

**Suspension Mounting Method:**

Hook

**Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:**

Any acceptable

**Chain Material Diameter:**

Any acceptable

**Mounting Position:**

Swivel

**Cooling Method:**

Any acceptable

**Voltage In Volts:**

230.0

**Phase:**

Three

**Special Features:**

10.0 ft h of lift; hooks w/safety latches; push button pendant control; upper limit @switch; 30 minutes 55.0 degree c motor temperature rise; weight 113.0 lbs

**Frequency In Hertz:**

60.0

**Nongovernment Document Data:**

Hmi400-18878

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02800