

View Online at <https://aerobasegroup.com/nsn/3950-00-907-6406>

Prime Mover Quantity:

1

Current Type:

Ac

Environmental Protection:

Any acceptable

Chain Type:

Proof coil

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Load Limit At Selected Speed And Drum Location:

2000.0 pounds single speed first drum

Travel Rate Per Minute:

16.0 feet

Mechanical Advantage Method:

Multiple gear

Braking Method:

Automatic

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Power Requirement Rating:

1.000 horsepower

Suspension Mounting Method:

Hook

Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:

Any acceptable

Chain Material Diameter:

Any acceptable

Mounting Position:

Swivel

Cooling Method:

Any acceptable

Voltage In Volts:

230.0

Phase:

Three

Special Features:

10.0 ft h of lift; hooks w/safety latches; push button pendant control; upper limit @switch; 30 minutes 55.0 degree c motor temperature rise; weight 113.0 lbs

Frequency In Hertz:

60.0

Nongovernment Document Data:

Hmi400-18878

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800