NSN 3950-00-936-5485

Chain Hoist - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3950-00-936-5485

| Prime Mover Quantity: | | | |
|---|--|--|--|
| 1 | | | |
| Current Type: | | | |
| Ac | | | |
| Unpackaged Unit Length: | | | |
| 22.750 inches | | | |
| Unpackaged Unit Width: | | | |
| 7.875 inches | | | |
| Unpackaged Unit Height: | | | |
| 8.375 inches | | | |
| Chain Type: | | | |
| Proof coil | | | |
| Inclosure Type: | | | |
| Fully enclosed | | | |
| Duty Cycle: | | | |
| Continuous | | | |
| Operation Method: | | | |
| Electrical | | | |
| Hook Quantity: | | | |
| 1 | | | |
| Load Element Quantity Per Hook: | | | |
| 1 | | | |
| Power Requirement Rating: | | | |
| 1.00 horsepower | | | |
| Suspension Mounting Method: | | | |
| Hook | | | |
| Maximum Traversing Speed: | | | |
| 16.0 feet per minute | | | |
| Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface: | | | |
| 18.000 inches | | | |
| Maximum Load Rating: | | | |
| 2000.0 pounds | | | |
| Mounting Position: | | | |
| Parallel | | | |
| Cooling Method: | | | |
| Air to air cooled | | | |
| Voltage In Volts: | | | |
| 115.0 and 230.0 | | | |
| Phase: | | | |
| Single | | | |
| Special Features: | | | |
| Hand control pushbutton station; w/ standard 10.0ft lift and 6.0ft drop | | | |

NSN 3950-00-936-5485

Chain Hoist - Page 2 of 2



| Frequency | In F | lertz: |
|-----------|------|--------|
|-----------|------|--------|

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800