

View Online at <https://aerobasegroup.com/nsn/3950-01-013-1449>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Environmental Protection:**

Splash proof

**Chain Type:**

Proof coil

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Power

**Travel Rate Per Minute:**

16.0 feet

**Mechanical Advantage Method:**

Spur gear

**Braking Method:**

Electric

**Hook Quantity:**

2

**Load Element Quantity Per Hook:**

2

**Center To Center Distance Between Load Elements:**

17.000 feet

**Power Requirement Rating:**

1.00 horsepower

**Suspension Mounting Method:**

Hook

**Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:**

17.000 inches

**Maximum Load Rating:**

2000.0 pounds

**Mounting Position:**

Parallel

**Cooling Method:**

Self-ventilated

**Voltage In Volts:**

220.0 and 440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800