

View Online at <https://aerobasegroup.com/nsn/3950-01-027-0017>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 motor controller and 2 self-locking hook

Environmental Protection:

Splashtight

Chain Type:

Proof coil

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Load Limit At Selected Speed And Drum Location:

1000.0 pounds single speed first drum

Travel Rate Per Minute:

16.0 feet

Mechanical Advantage Method:

Spur gear

Braking Method:

Manual

Hook Quantity:

2

Load Element Quantity Per Hook:

2

Center To Center Distance Between Load Elements:

Between 1.500 feet and 10.000 feet

Power Requirement Rating:

0.500 horsepower

Suspension Mounting Method:

Hook

Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:

18.000 inches

Chain Material Diameter:

0.312 inches

Maximum Load Rating:

1000.0 pounds

Mounting Position:

Right angle

Cooling Method:

Blower cooled

Voltage In Volts:

115.0 and 230.0

Phase:

Single

Special Features:

6 ft strain cable in control cord and 24v push button control unit station attached

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800