

View Online at <https://aerobasegroup.com/nsn/3950-01-052-2438>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 motor controller and 1 safety snap hook

Environmental Protection:

Any acceptable

Maximum Lift Height:

12.9 feet

Flange Width:

4.000 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Continuous

Operation Method:

Power

Load Limit At Selected Speed And Drum Location:

6000.0 pounds single speed first drum

Travel Rate Per Minute:

20.0 feet

Mechanical Advantage Method:

Spur gear

Braking Method:

Electric

Hook Quantity:

1

Load Element Quantity Per Hook:

2

Power Requirement Rating:

4.00 horsepower

Suspension Mounting Method:

Trolley

Trolley Suspension Style:

Geared, railtrack, flat flange

Trolley Type:

Motor driven

Maximum Traversing Speed:

70.0 feet per minute

Track Height:

8.000 inches

Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:

26.500 inches

Wheel Center To Center Distance:

10.500 inches

Maximum Load Rating:

6000.0 pounds

Mounting Position:

Parallel

Cooling Method:

Any acceptable

Voltage In Volts:

208.0 and 230.0

Phase:

Three

Special Features:

W/25 ft power cable and rewind reel

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800