

View Online at <https://aerobasegroup.com/nsn/3950-01-052-2438>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Furnished Items And Quantity:**

1 motor controller and 1 safety snap hook

**Environmental Protection:**

Any acceptable

**Maximum Lift Height:**

12.9 feet

**Flange Width:**

4.000 inches

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Continuous

**Operation Method:**

Power

**Load Limit At Selected Speed And Drum Location:**

6000.0 pounds single speed first drum

**Travel Rate Per Minute:**

20.0 feet

**Mechanical Advantage Method:**

Spur gear

**Braking Method:**

Electric

**Hook Quantity:**

1

**Load Element Quantity Per Hook:**

2

**Power Requirement Rating:**

4.00 horsepower

**Suspension Mounting Method:**

Trolley

**Trolley Suspension Style:**

Geared, railtrack, flat flange

**Trolley Type:**

Motor driven

**Maximum Traversing Speed:**

70.0 feet per minute

**Track Height:**

8.000 inches

**Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:**

26.500 inches

**Wheel Center To Center Distance:**

10.500 inches

**Maximum Load Rating:**

6000.0 pounds

**Mounting Position:**

Parallel

**Cooling Method:**

Any acceptable

**Voltage In Volts:**

208.0 and 230.0

**Phase:**

Three

**Special Features:**

W/25 ft power cable and rewind reel

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02800