

View Online at <https://aerobasegroup.com/nsn/3950-01-057-0416>

Prime Mover Quantity:

1

Current Type:

Ac

Environmental Protection:

Any acceptable

Maximum Lift Height:

52.0 feet

Flange Width:

6.000 inches

Unpackaged Unit Length:

55.188 inches

Unpackaged Unit Width:

34.750 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Continuous

Operation Method:

Power

Braking Method:

Electric

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Power Requirement Rating:

3.00 horsepower

Suspension Mounting Method:

Trolley

Trolley Suspension Style:

Plain, wide flange i beam wheels vertical

Trolley Type:

Motor driven

Maximum Traversing Speed:

20.0 feet per minute

Track Height:

15.000 inches

Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:

23.500 inches

Wheel Center To Center Distance:

27.625 inches

Maximum Load Rating:

2000.0 pounds

Mounting Position:

Parallel

Cooling Method:

Any acceptable

Voltage In Volts:

460.0

Phase:

Three

Frequency In Hertz:

60.0

Cognizant Service:

Usaf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800