

View Online at <https://aerobasegroup.com/nsn/3950-01-082-3762>

Prime Mover Quantity:

1

Current Type:

Ac

Environmental Protection:

Any acceptable

Maximum Lift Height:

20.0 feet

Flange Width:

0.500 inches

Chain Type:

Proof coil

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Continuous

Operation Method:

Power

Load Limit At Selected Speed And Drum Location:

1000.0 pounds single speed first drum

Travel Rate Per Minute:

32.0 feet

Braking Method:

Electric

Hook Quantity:

1

Load Element Quantity Per Hook:

2

Power Requirement Rating:

1.00 horsepower

Suspension Mounting Method:

Trolley

Trolley Suspension Style:

Geared, railtrack, flat flange

Trolley Type:

Plain

Track Height:

5.125 inches

Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:

17.250 inches

Wheel Center To Center Distance:

5.250 inches

Chain Material Diameter:

0.250 inches

Mounting Position:

Any acceptable

Cooling Method:

Self-ventilated

Voltage In Volts:

208.0

Phase:

Three

Frequency In Hertz:

50.0 and 60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800