NSN 3950-01-185-9371

Wire Rope Hoist - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3950-01-185-9371

Operation Method: Hand Mechanical Advantage Method: Lever Hook Quantity: 3 Load Element Quantity Per Hook: 1 Suspension Mounting Method: Hook Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface: Between 17.000 inches and 22.000 inches Maximum Load Rating: 3400.0 pounds
Mechanical Advantage Method: Lever Hook Quantity: 3 Load Element Quantity Per Hook: 1 Suspension Mounting Method: Hook Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface: Between 17.000 inches and 22.000 inches Maximum Load Rating:
Lever Hook Quantity: Load Element Quantity Per Hook: Suspension Mounting Method: Hook Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface: Between 17.000 inches and 22.000 inches Maximum Load Rating:
Hook Quantity: 3 Load Element Quantity Per Hook: 1 Suspension Mounting Method: Hook Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface: Between 17.000 inches and 22.000 inches Maximum Load Rating:
Load Element Quantity Per Hook: Suspension Mounting Method: Hook Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface: Between 17.000 inches and 22.000 inches Maximum Load Rating:
Load Element Quantity Per Hook: Suspension Mounting Method: Hook Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface: Between 17.000 inches and 22.000 inches Maximum Load Rating:
Suspension Mounting Method: Hook Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface: Between 17.000 inches and 22.000 inches Maximum Load Rating:
Suspension Mounting Method: Hook Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface: Between 17.000 inches and 22.000 inches Maximum Load Rating:
Hook Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface: Between 17.000 inches and 22.000 inches Maximum Load Rating:
Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface: Between 17.000 inches and 22.000 inches Maximum Load Rating:
Between 17.000 inches and 22.000 inches Maximum Load Rating:
Maximum Load Rating:
3400.0 pounds
Mounting Position:
Any acceptable
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A02800