

View Online at <https://aerobasegroup.com/nsn/3950-01-196-3271>

Prime Mover Quantity:

1

Current Type:

Ac

Environmental Protection:

Any acceptable

Maximum Lift Height:

10.0 feet

Chain Type:

Die lock link

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Travel Rate Per Minute:

8.0 feet

Mechanical Advantage Method:

Planetary gear

Braking Method:

Electric

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Power Requirement Rating:

2.00 horsepower

Suspension Mounting Method:

Hook

Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:

24.400 inches

Maximum Load Rating:

6600.0 pounds

Mounting Position:

Any acceptable

Cooling Method:

Self-ventilated

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

Pushbutton control; heavy duty disc brake; hoist duty motor includes overload protection through controlled torque design; upper and lower overtravel limit stop

Frequency In Hertz:

60.0

Cognizant Service:

Usaf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800