

View Online at <https://aerobasegroup.com/nsn/3950-01-196-3271>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Environmental Protection:**

Any acceptable

**Maximum Lift Height:**

10.0 feet

**Chain Type:**

Die lock link

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Power

**Travel Rate Per Minute:**

8.0 feet

**Mechanical Advantage Method:**

Planetary gear

**Braking Method:**

Electric

**Hook Quantity:**

1

**Load Element Quantity Per Hook:**

1

**Power Requirement Rating:**

2.00 horsepower

**Suspension Mounting Method:**

Hook

**Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:**

24.400 inches

**Maximum Load Rating:**

6600.0 pounds

**Mounting Position:**

Any acceptable

**Cooling Method:**

Self-ventilated

**Voltage In Volts:**

230.0 and 460.0

**Phase:**

Three

**Special Features:**

Pushbutton control; heavy duty disc brake; hoist duty motor includes overload protection through controlled torque design; upper and lower overtravel limit stop

**Frequency In Hertz:**

60.0

**Cognizant Service:**

Usaf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02800