NSN 3950-01-202-5578

Chain Hoist - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3950-01-202-5578

Prime Mover Quantity:
1
Current Type:
Ac
Environmental Protection:
Splash proof
Chain Type:
Die lock link
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Duty Cycle:
Continuous
Operation Method:
Power
Travel Rate Per Minute:
8.0 feet
Hook Quantity:
2
Load Element Quantity Per Hook:
2
Power Requirement Rating:
1.00 horsepower
Suspension Mounting Method:
Suspension Mounting Method: Hook
_
Hook
Hook Cooling Method:
Hook Cooling Method: Air to air cooled
Hook Cooling Method: Air to air cooled Voltage In Volts:
Hook Cooling Method: Air to air cooled Voltage In Volts: 230.0
Hook Cooling Method: Air to air cooled Voltage In Volts: 230.0 Phase:
Hook Cooling Method: Air to air cooled Voltage In Volts: 230.0 Phase: Three
Hook Cooling Method: Air to air cooled Voltage In Volts: 230.0 Phase: Three Frequency In Hertz:
Hook Cooling Method: Air to air cooled Voltage In Volts: 230.0 Phase: Three Frequency In Hertz: 60.0
Hook Cooling Method: Air to air cooled Voltage In Volts: 230.0 Phase: Three Frequency In Hertz: 60.0 Shelf Life:
Hook Cooling Method: Air to air cooled Voltage In Volts: 230.0 Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a
Hook Cooling Method: Air to air cooled Voltage In Volts: 230.0 Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a
Hook Cooling Method: Air to air cooled Voltage In Volts: 230.0 Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a Unit Of Measure:
Hook Cooling Method: Air to air cooled Voltage In Volts: 230.0 Phase: Three Frequency In Hertz: 60.0 Shelf Life: N/a Unit Of Measure: Demilitarization: