NSN 3950-01-206-2616

Windlass - Page 1 of 2

Prime Mover Quantity:

Current Type:



View Online at https://aerobasegroup.com/nsn/3950-01-206-2616

Ac
Environmental Protection:
Waterproof
Cubic Measure:
2.00 cubic feet
Chain Type:
Die lock link
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Duty Cycle:
Intermittent
Operation Method:
Power
Capstan Spool Mounting Position:
Horizontal
Capstan Spool Style:
Single head
Capstan Spool Surface Design:
Plain
Capstan Spool Quantity:
1
Whelped Wheel Quantity:
1
Err Default:
Err default
Travel Rate Per Minute:
34.0 feet and 30.0 feet
Braking Method:
Electric
Err Default:
Err default
Power Requirement Rating:
1.50 horsepower
Largest Diameter And Location:
7.000 inches first spool
Overall Length And Location:
6.500 inches first spool

NSN 3950-01-206-2616

Windlass - Page 2 of 2



Chain Material Diameter:
0.500 inches
Cooling Method:
Air to air cooled
Voltage In Volts:
440.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A02800