

View Online at <https://aerobasegroup.com/nsn/3950-01-218-1789>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Environmental Protection:**

Dripproof and watertight

**Maximum Lift Height:**

30.0 feet

**Flange Width:**

Between 4.000 inches and 7.000 inches

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Continuous

**Travel Rate Per Minute:**

21.0 feet

**Braking Method:**

Electric

**Hook Quantity:**

1

**Load Element Quantity Per Hook:**

1

**Power Requirement Rating:**

3.00 horsepower

**Suspension Mounting Method:**

Trolley

**Trolley Suspension Style:**

Geared, railtrack sloped flange

**Trolley Type:**

Motor driven

**Track Height:**

Between 8.000 inches and 24.000 inches

**Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:**

13.000 inches

**Maximum Load Rating:**

4000.0 pounds

**Mounting Position:**

Parallel

**Cooling Method:**

Air to air cooled

**Voltage In Volts:**

220.0 and 440.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800