

View Online at <https://aerobasegroup.com/nsn/3950-01-221-8839>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Environmental Protection:**

Any acceptable

**Maximum Lift Height:**

20.0 feet

**Flange Width:**

7.000 inches

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Continuous

**Hook Quantity:**

1

**Load Element Quantity Per Hook:**

1

**Power Requirement Rating:**

5.00 horsepower

**Suspension Mounting Method:**

Trolley

**Trolley Suspension Style:**

Geared, standard i beam, wheels, vertical

**Trolley Type:**

Motor driven

**Maximum Traversing Speed:**

15.0 feet per minute

**Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:**

28.000 inches

**Wheel Center To Center Distance:**

9.000 inches

**Maximum Load Rating:**

10000.0 pounds

**Mounting Position:**

Parallel

**Cooling Method:**

Blower cooled

**Voltage In Volts:**

460.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02800