

View Online at <https://aerobasegroup.com/nsn/3950-01-236-5967>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Environmental Protection:**

Any acceptable

**Chain Type:**

Proof coil

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Continuous

**Operation Method:**

Power

**Load Limit At Selected Speed And Drum Location:**

2000.0 pounds single speed first drum

**Travel Rate Per Minute:**

8.0 feet

**Mechanical Advantage Method:**

Spur gear

**Braking Method:**

Electric

**Hook Quantity:**

2

**Load Element Quantity Per Hook:**

1

**Power Requirement Rating:**

0.50 horsepower

**Suspension Mounting Method:**

Hook

**Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:**

18.625 inches

**Chain Material Diameter:**

Any acceptable

**Maximum Load Rating:**

2000.0 pounds

**Mounting Position:**

Any acceptable

**Cooling Method:**

Air to air cooled

**Voltage In Volts:**

110.0

**Phase:**

Single

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A02800