

View Online at <https://aerobasegroup.com/nsn/3950-01-251-5427>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Environmental Protection:**

Any acceptable

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Operation Method:**

Power

**Travel Rate Per Minute:**

16.0 feet

**Braking Method:**

Electric

**Hook Quantity:**

2

**Load Element Quantity Per Hook:**

1

**Power Requirement Rating:**

0.250 horsepower

**Suspension Mounting Method:**

Hook

**Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:**

14.250 inches

**Chain Material Diameter:**

Any acceptable

**Maximum Load Rating:**

500.0 pounds

**Mounting Position:**

Any acceptable

**Cooling Method:**

Air to air cooled

**Voltage In Volts:**

440.0

**Special Features:**

Three phase, duty cycle of 30 minutes, the chain type is carborized steel; the mechanical advantage method-alloy steel lift wheel, two gear reduction

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02800