NSN 3950-01-251-6119

Chain Hoist - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3950-01-251-6119

Furnished Items And Quantity: 1 automatic safety brake Power Drive Operating Pressure: Any acceptable Maximum Lift Height: 10.0 feet Chain Type: Proof coil Prime Mover Type: Pneumatic motor Operation Method: Power Mechanical Advantage Method: Planetary gear Braking Method: Manual Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
1 automatic safety brake Power Drive Operating Pressure: Any acceptable Maximum Lift Height: 10.0 feet Chain Type: Proof coil Prime Mover Type: Pneumatic motor Operation Method: Power Mechanical Advantage Method: Planetary gear Braking Method: Manual Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Power Drive Operating Pressure: Any acceptable Maximum Lift Height: 10.0 feet Chain Type: Proof coil Prime Mover Type: Pneumatic motor Operation Method: Power Mechanical Advantage Method: Planetary gear Braking Method: Manual Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Any acceptable Maximum Lift Height: 10.0 feet Chain Type: Proof coil Prime Mover Type: Pneumatic motor Operation Method: Power Mechanical Advantage Method: Planetary gear Braking Method: Manual Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Maximum Lift Height: 10.0 feet Chain Type: Proof coil Prime Mover Type: Pneumatic motor Operation Method: Power Mechanical Advantage Method: Planetary gear Braking Method: Manual Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Chain Type: Proof coil Prime Mover Type: Pneumatic motor Operation Method: Power Mechanical Advantage Method: Planetary gear Braking Method: Manual Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Chain Type: Proof coil Prime Mover Type: Pneumatic motor Operation Method: Power Mechanical Advantage Method: Planetary gear Braking Method: Manual Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Proof coil Prime Mover Type: Pneumatic motor Operation Method: Power Mechanical Advantage Method: Planetary gear Braking Method: Manual Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Prime Mover Type: Pneumatic motor Operation Method: Power Mechanical Advantage Method: Planetary gear Braking Method: Manual Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Pneumatic motor Operation Method: Power Mechanical Advantage Method: Planetary gear Braking Method: Manual Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Operation Method: Power Mechanical Advantage Method: Planetary gear Braking Method: Manual Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Power Mechanical Advantage Method: Planetary gear Braking Method: Manual Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Mechanical Advantage Method: Planetary gear Braking Method: Manual Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Planetary gear Braking Method: Manual Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Braking Method: Manual Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Manual Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Hook Quantity: 2 Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Load Element Quantity Per Hook: Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Load Element Quantity Per Hook: 2 Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Suspension Mounting Method: Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Lug Chain Material Diameter: Any acceptable Maximum Load Rating:
Chain Material Diameter: Any acceptable Maximum Load Rating:
Any acceptable Maximum Load Rating:
Maximum Load Rating:
4400.0
4400.0 pounds
Mounting Position:
Parallel
Cooling Method:
Air to air cooled
Special Features:
Latch type hooks and two-piece, single-line hook block
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A02800